

cMT-SVRX-820

cMT-SVRX-822

cMT X Headless



Key Features

- ▶ Supports cMT Viewer
- ▶ Supports OPC UA Server
- ▶ COM port × 3, Ethernet port × 2, USB host port × 1, microSD slot × 1
- ▶ Built-in 4 GB FLASH and 1 GB RAM
- ▶ Fan-less cooling system
- ▶ cMT-SVRX-822: Built-in EasyAccess 2.0 License

Technical Specifications

Memory

FLASH	4 GB
RAM	1 GB

Processor

CPU	Quad-core RISC
-----	----------------

I/O Port

Memory Card Type	microSD × 1
USB Host	USB 2.0 × 1
Ethernet	LAN 1: 10/100/1000 Base-T × 1 LAN 2: 10/100 Base-T × 1
COM Port	COM1: RS-232 2W COM2: RS-485 2W/4W COM3: RS-485 2W
WiFi	N/A
RS-485 Dual Isolation	N/A
CAN Bus	N/A
Audio Output	N/A

Power

Input Power	24 ± 20 % VDC
Power Isolation	Built-in
Power Consumption	850 mA @ 24 VDC
Voltage Resistance	500 VAC (1 min.)
Isolation Resistance	Exceed 50 MΩ at 500 VDC

Mechanical

Enclosure	Plastic
Dimensions W×H×D	29.8 × 130 × 115 mm
Weight	Approx. 0.24 kg
Mount	35 mm DIN rail mounting

Environment

PCB Coating	Yes
Protection Structure	IP20
Storage Temperature	-20° ~ 60°C (-4° ~ 140°F)
Operating Temperature	0° ~ 50°C (32° ~ 122°F)
Relative Humidity	10 % ~ 90 % (non-condensing)
Altitude	3,000 m
Vibration Endurance	10 to 25 Hz (X, Y, Z direction 2G 30 minutes)

Product Carbon Footprint (kg CO₂e)

Manufacturing Stage (A1-A3)	18
-----------------------------	----

Certificate


CE	CE Marked
UL	cULus Listed

Software

EasyBuilder Pro	V6.07.01 or later versions
Weincloud	EasyAccess 2.0 (Optional), Dashboard (Optional)
CODESYS®	Optional

* CODESYS® is a trademark of CODESYS GmbH.

Dimensions



1	USB Host
2	LAN 2
3	LAN 1
4	COM1: RS-232 2W, COM2: RS-485 2W/4W, COM3: RS-485 2W

5	Power Connector
6	DIP Switch
7	Reset Button
8	microSD Card Slot

Pin Assignment

COM: 9 Pin, D-sub, Male

PIN#	COM1 [RS232]2W	COM2 [RS485]2W	COM2 [RS485]4W	COM3 [RS485]2W
1				Data+
2	RxD			
3	TxD			
4				Data-
5	GND			
6		Data+	Rx+	
7		Data-	Rx-	
8			Tx+	
9			Tx-	

Part Number

☐ **【cMT-SVRX-820】**

Built-in 4 GB FLASH / 1 GB RAM, 10/100/1000 M Ethernet port × 1, 10/100 M Ethernet port × 1

☐ **【cMT-SVRX-822】**

Built-in 4 GB FLASH / 1 GB RAM, 10/100/1000 M Ethernet port × 1, 10/100 M Ethernet port × 1, built-in EasyAccess 2.0 license

Optional:

☐ **RZACEA020:** EasyAccess 2.0 Activation Card (cMT-SVRX-820)

☐ **RZ0CDS000:** CODESYS License